



KTI. PROJEKT Nº 511

E. Karamuk¹, J. Mayer¹, B. Selm², B. Bischoff³, R. Ferrario³, M. Heller⁴, M. Billia⁴, R. Seidel⁵, M. Wanner⁶ and R. Moser⁷.

1 Biocompatible Materials Science and Engineering, ETH Zürich, 2 Swiss Federal Laboratories for Materials Testing and Research, St. Gallen, 3 Bischoff Textil AG, St. Gallen, 4 TISSUPOR AG, St.Gallen, 5 Swiss Textile College, Wattwil, 6 Swiss Paraplegics Foundation, Nottwil (SPZN), 7 IBR, Matzingen

TISSUPOR: Development of a structured wound dressing based on a textile composite functionalised by embroidery technology

Introduction



Motivation

The aim of this project is the development of a new, textile

Clinical experiences

Decubitus was treated at the wound care clinic of the Swiss Paraplegic Centre, Nottwil, according to internal protocols. After initial debridement wounds were treated with TISSUPOR until 50 % wound surface reduction was achieved. First results show a comparable healing rate compared to conventional moist wound care. However the concept of TISSUPOR resulted in much less frequent dressing changement (2 times per week instead of twice a day). Our working hypothesis of induced bleeding during dressing changement could be veryfied. Right side: Example of wound treatment with TISSUPOR. Female patient, age 69, with decubitus. Wound volume after one week was 80ml. The dressing was changed twice a week. The wound was surgically closed after 3.5 weeks.



based wound dressing system to be applied for chronically non healing wounds e.g. ulcus cruris and pressure sores. Non healing wounds have a great economic impact because they need intensive wound care for very long periods, often disabling the patient and causing high health care costs.



Design of techn. embroidery for the wound dressing

One of the key issues in tissue regeneration of chronically non healing wounds is controlled revascularisation of the epidermal tissue. In textile implant materials tissue formation and vascularisation depend on the size and distribution of pores and fibers. An arrangement of pores of different orders of magnitude, ranging from 1μm to 1000μm will favour the tissue ingrowth and the formation of new blood wessels and capillaries [1]. Embroidery technology allowed to achieve a 3-dimensionally structured textile architecture that combines pores for directed angiogenesis and elements for local mechanical stimulation.

application time 2 weeks wound volume 40ml



Histological analysis of the wound after removal of TISSUPOR: Punch biopsies from the wound base (A) show three histologically distinct zones (B). The granulation tissue (C, D, taken from zone II) contains a dense network of capillaries (arrows in D).

Clinical screening study: in-use test covering various indications

The aim of this study was to screen possible applications of the embroidered wound dressing and to define the most promising indications for successful treatment.

Additionally the combination with standard therapies such as vacuum therapy was of special interest. A total of 196 patients were treated in different European clinics. The study covered mostly chronic wounds, but also post-operative acute wounds e.g. after tumor excision were treated. The wound dressing was applied according to the protocols of the individual clinic. In all cases the state of the wound was documented at each wound pad exchange. The average treatment time was 25 days, ranging from 6 days to 8 weeks.



Integrated stiff elements for mechanical stimulation of the wound (Polyamide monofilament, 150µm Ø).

Pore sizes $500\mu m$ to $3000\mu m$: Uptake of blood coagula and formation of granulation tissue.



acute wounds (n=65) chronic wounds (n=131)

For acute wounds (left chart) a positive effect of the wound dressing was observed in over 90% of the cases. The application of TISSUPOR was found to rapidly induce new granulation tissue which represents a vital base for surgical wound closure. In chronic cases (right chart) the strongest effect was seen in fibrin covered wounds. Almost 80% of these wounds were clean or granulating at the end of the therapy. No improvement was found in necrotic and infected wounds.

Treatment of large skin defect with TISSUPOR after skin tumor excision. A: state of the wound at begin of therapy. B: state at first dressing exchange after 7 days: initiation of wound granulation is observed. The skin around the wound edge is slightly irritated. C: wound state at second exchange after 14 days: intensive granulation is observed.

Treatment of large defect due to phlegmone and necrotic osteomyelitis. The embroidered wound dressing was combined with vacuum therapy. A: state of the wound at begin of therapy.

B: first dressing exchange after 3 days shows intensive granulation. The imprint of the embroidered textile structure is clearly visible. C: after 24 days the wound area is significantly reduced and vital granulation tissue is visible

Outlook

PGA

washed in

aceton

Textile structure and mechanics

Image analysis methods are investigated to quantify strain patterns in textiles. Synchtrotron µ-CT is used to measure structural parameters like porosity or specific surface structure.

Tissue Engineering

Further development of TISSUPOR

Investigation of the biological effects of **TISSUPOR**

Biodegradable embroidered textiles

Degradation of yarn material is a key question in the design of textile cell carriers for tissue engineering. To demonstrate the use of embroidery technology as a tool for processing of biomaterials we used poly(glycolic acid) (PGA) yarns (left). The removal of the base cloth did not change the tensile properties of the yarn if we stiched onto a nonwoven poly(venyl alcohol) PGA PGA tissue which was washed out in water at ambient temuntreated washed in H2O perature for several hours.

The adaptation of the industrial embroidery process to medical textiles requires thorough biocompatibility testung to find possible toxic effects of chemical residues from machine, base cloth or yarn sizing. We performed basic cytotoxicity assays using a 3T3 fibroblast cell line. In direct (right) and indirect (left) exposure methods, endpoints of mitochondric activity (MTT) and cell mass (DNA) were measured. In both experiments no significant toxic effects could be detected.

Ferrario et Karamuk fecunt 2001

Embroidered scaffolds serve as test systems to study cell/textile interactions in vitro. Influence of mechanical stimulation and material degradation (bottom, left) is investigated. Primary rat tendon fibroblasts (right, top and bottom) are cultured on a circular scaffold that is designed to fit into standard cell culture plates (top, left).

Further clinical and biological studies must concentrate on direct comparison with established therapies to quantitatively analyze a clinical benefit. The biological effect of mechanical stimulation on the formation of granulation tissue remains unclear. Therefore the interactions of the textile structure and the wound dressing have to be further investigated on a cellular and molecular level in order to define the biomechanical factors which are inducing the prominent angiogenesis. Furthermore, the quality of the developing connective tissue with respect to possible scar formation remains an open question.

Evaluation of strategies for wound epithelialization Different approaches will be investigated in feasibility studies to define an optimal concept for wound closure after formation of highly vascularized granulation tissue with TISSUPOR. Possible further developments include the local delivery of angiogenic, antibiotic or pain reducing factors from degradable yarns. Additionally, the possibility to stitch with conductive fibers in a defined pattern opens new ways in electrotherapy.

References

[1] Wintermantel E., Cima L., Schloo B., Langer R. (1992), Angiopolarity of cell carriers. Directional angiogenesis in resorbable liver cell transplantation devices, in: R. Steiner, B. Weisz and R. Langer, eds., Angiogenesis: Principles-Science-Technology-Medicine, Birkhäuserverlag Basel, 331-334. [2] Wintermantel, E., Mayer, J., Blum, J., Eckert, K.-L., Lüscher, P., Mathey, M. (1996), Tissue engineering scaffolds using superstructures, Biomaterials, 17, 83-92.

[3] Karamuk, E., Mayer, Düring, M., Wagner, B., Ferrario, R., Bischoff, B., Billia, M., Seidl, R. and Wintermantel, E., Embroidery Technology for Medical Textiles, Medical Textiles '99, Bolton 1999.

[4] Karamuk E., Mayer, J. (2000) Embroidery technology for medical textiles and tissue engineering, Technical Textiles International, 9,9-13.

[5] Karamuk E. (2001) Embroidered Textiles for Medical Applications, DIss ETH No 14257. [6] Karamuk E., Mayer J., (2001) Embr. based vital/avital composites for tissue engineering ICCM 13, Beijing.

Acknowledgements

This study is supported by the MedTech Initiative of the Swiss Federal Office for Professional Education and Technology.

 μ -CT measurement and reconstruction by P. Thurner (ETH-BWB) and F. Beckmann (HASYLAB, Hamburg)